

SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

CHEMICAL PRODUCT IDENTIFICATION:

PRODUCT NAME CODE . . . : 41000 NICK-FIX PLUMBING WHITE / 41001 NICK-FIX APPLIANCE WHITE
41041 NICK-FIX ALMOND / 41042 NICK-FIX BONE
41043 NICK-FIX AVOCADO / 41044 NICK-FIX HARVEST GOLD
41045 NICK-FIX BLACK / C9 NICK-FIX COBALT
PRODUCT CLASS : Touch-Up Bottle

MSDS PREPARATION DATE : 01/01/2011

MANUFACTURER IDENTIFICATION:
MULTI-TECH PRODUCTS CORPORATION
41519 CHERRY STREET
MURRIETA CA 92562

EMERGENCY TELEPHONE NUMBERS:
24 HOURS A DAY - CALL CHEMTREC : 800-424-9300
INTERNATIONAL CALLS TO CHEMTREC : 703-527-3887
8 AM TO 4:30 PM PACIFIC TIME : 951-834-9066

SECTION 2 - COMPOSITION, INFORMATION ON INGREDIENTS

1 ETHYLBENZENE
CAS# 100-41-4
ETHYLBENZENE
PCT BY WT: 1.0740 VAPOR PRESSURE: 19.000 MMHG @ 68F LEL 1.20
EXPOSURE LIMIT:
ACGIH TLV-TWA 100 ppm
ACGIH TLV-STEL 125 ppm
OSHA PEL-TWA 100 ppm
OSHA PEL-STEL 125 ppm
OTHER IARC (2B)

2 Methyl Isobutyl Ketone
CAS# 108-10-1
4-Methyl-2-pentanone
PCT BY WT: 2.0000 VAPOR PRESSURE: 16.000 MMHG @ 68F LEL 1.20
EXPOSURE LIMIT:
ACGIH TLV-TWA 50 ppm
ACGIH TLV-STEL 75 ppm
OSHA PEL-TWA 100 ppm
OSHA PEL-STEL N/A
COMPANY N/A

3 2-PENTANONE
CAS# 107-87-9
2-PENTANONE
PCT BY WT: 19.0000 LEL 1.50
EXPOSURE LIMIT:
ACGIH TLV-TWA 200 ppm
ACGIH TLV-STEL 250 ppm
OSHA PEL-TWA 200 ppm
COMPANY N.E.

4 TITANIUM DIOXIDE
CAS# 13463-67-7
TITANIUM DIOXIDE
PCT BY WT: 10.0000
EXPOSURE LIMIT:
ACGIH TLV-TWA 10 mg/m3
ACGIH TLV-STEL NO INFO
OSHA PEL-TWA 10 mg/m3
COMPANY N.E.

5 XYLENE
CAS# 1330-20-7

XYLENE
PCT BY WT: 5.0000 VAPOR PRESSURE: 6.600 MMHG @ 68F LEL 1.00
EXPOSURE LIMIT:
ACGIH TLV-TWA 100 ppm
ACGIH TLV-STEL 150 ppm
OSHA PEL-TWA 100 ppm
OSHA PEL-STEL 150 ppm
COMPANY N.E.

6 ACRYLIC POLYMER

ACRYLIC POLYMER
PCT BY WT: 8.0000
EXPOSURE LIMIT:
ACGIH TLV-TWA N.E.
ACGIH TLV-STEL N.E.
OSHA PEL-TWA N.E.
COMPANY N.E.

7 BUTYL BENZYL PHTHALATE

CAS# 85-68-7
BUTYL BENZYL PHTHALATE
PCT BY WT: 2.0000 LEL .30
EXPOSURE LIMIT:
ACGIH TLV-TWA 5 mg/m3
ACGIH TLV-STEL N.E.
OSHA PEL-TWA 5 mg/m3

8 ACETONE

CAS# 67-64-1
ACETONE
PCT BY WT: 26.0000 VAPOR PRESSURE: 231.000 MMHG @ 68F LEL 2.60
EXPOSURE LIMIT:
ACGIH TLV-TWA 750 ppm
ACGIH TLV-STEL 1000 ppm
OSHA PEL-TWA 750 ppm
OSHA PEL-STEL 1000 ppm
COMPANY N.E.

9 ETHYLENE GLYCOL MONOPROPYL ETH

CAS# 2807-30-9
ETHYLENE GLYCOL MONOPROPYL ETHER
PCT BY WT: 3.0000 VAPOR PRESSURE: 1.200 MMHG @ 68F LEL 1.30
EXPOSURE LIMIT:
ACGIH TLV-TWA NO INFO
ACGIH TLV-STEL NO INFO

10 ETHYL 3-ETHOXYPROPIONATE

CAS# 763-69-9
ETHYL 3-ETHOXYPROPIONATE
PCT BY WT: 9.0000 VAPOR PRESSURE: 1.110 MMHG @ 68F LEL 1.10
EXPOSURE LIMIT:
ACGIH TLV-TWA 50 ppm
ACGIH TLV-STEL NONE EST.
OSHA PEL-TWA 50 ppm
COMPANY N.E.

11 GLYCOL ETHER PM ACETATE
CAS# 108-65-6
PROPYLENE GLYCOL METHYL ETHER ACETATE
PCT BY WT: 3.0000 VAPOR PRESSURE: 3.700 MMHG @ 68F LEL 1.30
EXPOSURE LIMIT:
ACGIH TLV-TWA NOT ESTABLISHED
ACGIH TLV-STEL NOT ESTABLISHED

This product contains one or more reported carcinogens or suspected carcinogens which are noted NTP, IARC, or OSHA-Z in the other limits recommended column.

This substance is classified as a hazardous air pollutant.

SECTION 3 - HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW:

- Harmful if swallowed.
- Harmful if inhaled.
- Causes eye irritation.
- Causes skin irritation.
- Vapors irritating to eyes and respiratory tract.
- Extremely flammable liquid and vapor.
- Vapors may cause flash fire or explosion.

POTENTIAL HEALTH EFFECTS:

EYE:

May cause severe eye irritation.

SKIN:

- May cause skin irritation.
- Prolonged or repeated contact may cause drying, cracking, or irritation of the skin.
- Product contains a component which can be absorbed through the skin.
- Excessive exposure may cause hemolysis (red blood cell damage) which can impair the blood's ability to transport oxygen.

INHALATION:

- Exposure to high concentrations of vapors may cause dizziness, breathing difficulty, headaches or respiratory irritation.
- Extremely high concentrations may cause drowsiness, staggering, confusion, unconsciousness, coma or death.
- Liquid or vapor may be irritating to skin, eyes, throat or lungs.
- Intentional misuse by deliberately concentrating and inhaling the contents of this product can be harmful or fatal.

INGESTION:

- Moderately toxic. May cause stomach discomfort, nausea, vomiting, diarrhea, and narcosis.
- Aspiration of material into the lungs if swallowed or if vomiting occurs can cause chemical pneumonitis which can be fatal.

CHRONIC EFFECTS:

- Chronic overexposure to a component or components in this material has been found to cause the following effects in laboratory animals:
 - Kidney damage
 - Eye damage
 - Liver damage
 - Anemia
- Chronic overexposure to a component or components in this product has been suggested as a cause of the following effects in humans:
 - Cardiac abnormalities

SECTION 7 - HANDLING AND STORAGE

HANDLING:

Wash hands thoroughly after handling.

STORAGE:

Store in a cool dry area with ventilation suitable for storing materials shown in section 2.

Keep away from heat, sparks and flame.

Store in a cool place away from direct sunlight or any source of ignition. Do not store at temperatures above 120 degrees F.

SECTION 8 - EXPOSURE CONTROLS, PERSONAL PROTECTION

ENGINEERING CONTROLS:

Sufficient ventilation, in volume and pattern, should be provided to keep air contamination below current applicable OSHA permissible exposure limit or ACGIH's TLV limit.

RESPIRATORY PROTECTION:

If workplace exposure limits are exceeded for any component(see section 2 for hazardous components and exposure limits), a NIOSH/OSHA approved respirator suitable for components listed is recommended.

SKIN PROTECTION:

Chemical resistant plastic or rubber gloves recommended for prolonged or repeated contact.

EYE PROTECTION:

Chemical goggles with side shields or face shield recommended if contact with the eyes is likely.

OTHER PROTECTIVE EQUIPMENT:

Appropriate impervious clothing is recommended if prolonged or repeated contact is likely.

HYGIENIC PRACTICES:

Wash hands before eating or smoking. Smoke in designated areas only.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Vapor Pressure : 231.00 mm Hg @ 20 C

Vapor Density : 3.70

Boiling Range : Lower - 133.0 øF
Higher - 999.0 øF

Specific Gravity : .972

Formula Weight per Volume : 8.0925 LB/GL

VOC (Calculated, LB/GAL) : 4.816

VOC (Calculated, GM/L). : 577.10

Percent Volatile by Weight. : 66.6783

Evaporation Rate : 7.700 (n-Butyl Acetate = 1)

Viscosity : -N/A

SECTION 10 - STABILITY AND REACTIVITY

CONDITIONS TO AVOID:

Avoid contact with heat, sparks, and open flame.

INCOMPATIBILITIES:

Strong oxidizing agents.

DECOMPOSITION:

Thermal decomposition may produce carbon dioxide, carbon monoxide, and unidentifiable organic materials.

POLYMERIZATION:

No hazardous polymerization will occur under normal conditions.

STABILITY:

The product is stable under normal storage conditions.

SECTION 11 - TOXICOLOGICAL INFORMATION

No specific information is available. Please refer to Section 3 for available information on potential health effects.

SECTION 12 - ECOLOGICAL INFORMATION

No specific ecological information is available for this product.

SECTION 13 - DISPOSAL CONSIDERATIONS

WASTE DISPOSAL:

Place in closed containers. Dispose of product in accordance with local, county, state, and federal regulations.

SECTION 14 - TRANSPORT INFORMATION

Ground shipment of limited or excepted quantities of aerosols or liquid paint in containers of 1 quart or less:

CONSUMER COMMODITY, ORM-D

Ground shipment of liquid paint in containers more than 1 quart:

PAINT, FLAMMABLE LIQUID, UN1263, CLASS 3, GROUP II

(Regulatory sources: DOT 49CFR 172.101)

Air shipment of limited or excepted quantities of aerosols or liquid paint in containers of 1 quart or less:

CONSUMER COMMODITY, ID 8000, CLASS 9 MISCELLANEOUS LABEL

(Regulatory sources: ATAI Quantity Exemptions - Table 2.8.4, 2.7.A, 2.7.5, Packaging Instruction: 910)

OR

AEROSOLS, FLAMMABLE, UN1950, CLASS 2.1 LABEL

(Regulatory sources: ATAI Quantity Exemptions - Table 2.8.1, 2.8.4, Packaging Instruction: Y203)

SECTION 15 - REGULATORY INFORMATION

SARA 313 INFORMATION:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

ETHYLBENZENE

CAS# 100-41-4 PCT BY WT: 1.0740

4-Methyl-2-pentanone

CAS# 108-10-1 PCT BY WT: 1.9000

XYLENE

CAS# 1330-20-7 PCT BY WT: 4.6960

ETHYLENE GLYCOL MONOPROPYL ETHER

CAS# 2807-30-9 PCT BY WT: 3.3700

FEDERAL REGULATIONS:

TOXIC SUBSTANCES CONTROL ACT: The chemical substances in this product are listed on the TSCA Section 8 inventory.

STATE REGULATIONS:

NEW JERSEY RIGHT-TO-KNOW

No non-hazardous ingredients are among the top five ingredients

PENNSYLVANIA RIGHT-TO-KNOW

No non-hazardous ingredients are present greater than 3%

INTERNATIONAL REGULATIONS:

CANADA: The chemical substances in this product are listed on the Canadian Domestic Substances List.

SECTION 16 - OTHER INFORMATION

The information contained on this MSDS is believed to be reliable and accurate. Due to the changing nature of government information, it is impossible to guarantee the accuracy of the information contained herein. Since the conditions of handling and use are beyond our control, we make no guarantee of results and assume no liability for damages incurred by the use of this material. This information should not be regarded as legal advice or regulation. It is the responsibility of the user to comply with all Federal, State, and Local laws and regulations. For questions relating to specific aspects of the requirements and regulations consult the proper regulatory agency.

HMIS RATINGS:

HEALTH: FLAMMABILITY: REACTIVITY: PERSONAL PROTECTION: